

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 939 566 A1

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 158(3) EPC

(43) Date of publication:
01.09.1999 Bulletin 1999/35

(21) Application number: 98938888.9

(22) Date of filing: 19.08.1998

(51) Int. Cl.⁶: H04Q 7/28, H04J 13/00

(86) International application number:
PCT/JP98/03666

(87) International publication number:
WO 99/09767 (25.02.1999 Gazette 1999/08)

(84) Designated Contracting States:
DE GB SE

(30) Priority: 19.08.1997 JP 22218297

(71) Applicant:
NTT MOBILE COMMUNICATIONS NETWORK
INC.
Minato-ku, Tokyo 105-8436 (JP)

(72) Inventors:
• UEBAYASHI, Shinji
Kanagawa 236-0057 (JP)

• ONOE, Seizo
Kanagawa 236-0032 (JP)
• NAGATSUKA, Minami,
Nishi-ku Yokohama-shi Kanagawa 220-0035 (JP)
• NAKAMURA, Takehiro,
Kanagawa 239-0841 (JP)

(74) Representative:
Beresford, Keith Denis Lewis et al
BERESFORD & Co.
2-5 Warwick Court
High Holborn
London WC1R 5DJ (GB)

(54) **SIGNAL TRANSMISSION METHOD AND BASE STATION DEVICE FOR MOBILE COMMUNICATIONS**

(57) A signal transmission method checks, when detecting an occurrence of a communication request, whether the communication request is a high speed communication (step S302). In the case of the high speed communication, it checks whether the number of current high speed communications (m) plus one is greater than the upper limit (m_{\max}) of the high speed communication (step S312). If greater, it cancels the request as a call loss (S316), and sets to a variable a the ratio (h) of the rate of the high speed communication to that of a low speed communication. If the communication request is the low speed communication, it sets one to the variable a (step S304). It compares n plus a with n_{\max} (step S306), where n is the total number of all the current communications, a is the value associated with the communication request, and n_{\max} is the upper limit of the number of communications acceptable in a bandwidth, all of which are expressed in terms of the number of the low speed communications. If n plus a is greater than n_{\max} , the communication request is canceled as a call loss (S316). Otherwise, the total number of the current high speed communications (m) and the total number of all the current communications (n) expressed in terms of the number of the low speed communications are updated, and a channel is assigned to the communication request (step S310).




FIG.3

EP 0 939 566 A1

Description

TECHNICAL FIELD

[0001] The present invention relates to signal transmission over traffic channels of cellular mobile communications simultaneously carrying out multiple communications between a base station and a plurality of mobile stations at different transmission rates, and more particularly to signal transmission which is effective in achieving simultaneous multiple communications in the same band at different transmission rates through forward channels in CDMA mobile communications.

BACKGROUND ART

[0002] Conventionally, voice communications have been a mainstream of the cellular mobile communications with data communications constituting only a small part thereof. The data communications taking place occasionally are handled at the same transmission rate as the voice communications. Recently, however, demand for high speed data communications has been sharply growing, highlighting a signal transmission method that carries out multiple communications at different transmission rates. Thus, not a few papers are published about this subject. For example, J. M. Harris and S. P. Kumar, "Scheduling to Meet Mixed Quality of Service Requirement in Wireless Networks", MoMuc, 1996, studied voice (low speed) communications and a signal transmission scheme over reverse traffic channels handling a mixture of data and image (high speed) communications, and proposed a method that separated in advance the voice traffic channels from image traffic channels. Considering actual mobile data communication services, however, it is expected that leading usage patterns are such that mobile stations access databases connected to a fixed network to read data. Accordingly, a signal transmission method over forward traffic channels becomes important. In addition, as a mobile communication scheme from now on, a CDMA scheme is promising because of its high frequency efficiency. It is possible for the forward traffic channels in the CDMA to achieve, besides the scheduling of transmission timings, orthogonalization of spreading codes, precise transmission power control considering the transmission power of other communications, and the like. The forward channels, however, undergo only insufficient study although they differ greatly from the reverse channels.

[0003] As described above, the signal transmission method for carrying out simultaneous multiple communications at different transmission rates is not yet in the practical use in the conventional cellular mobile communications. Although some papers examined it, an efficient signal transmission method has not yet been studied which integrally considers in the mobile communications the transmission power over the forward chan-

nels, the number of traffic channels and the balance between the forward and reverse traffic. In particular, only insufficient studies have been achieved of the CDMA mobile communication scheme which is promising from now on.

DISCLOSURE OF THE INVENTION

[0004] An object of the present invention is to provide a traffic channel allotting method for achieving efficient simultaneous communications at different transmission rates through forward channels in the same band.

[0005] To accomplish the object, the present invention is characterized by a signal transmission method over a forward traffic channel in cellular mobile communications that can simultaneously perform multiple communications between a plurality of mobile stations and a base station at different transmission rates, the signal transmission method comprising the steps of: detecting, on a base station side, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate; and rejecting the communication request for the high speed communication, if a total number of high speed communications transmitted simultaneously exceeds a predetermined fixed value when the detected communication request for the high speed communication is added.

[0006] Employing this configuration can limit the traffic of the high speed communications, thereby ensuring channels for low speed communication calls.

[0007] Here, it is possible to accept the new communication request if a total number of communications transmitted simultaneously is less than or equal to a predetermined fixed value when the detected communication request for the high speed communication is added, to temporarily hold the communication request if the total number is greater than the fixed value, and to accept the communication request after waiting until the total number of the communications becomes less than or equal to the fixed value.

[0008] This configuration limits by the delay the traffic of the high speed communications, thereby ensuring the channels for the low-speed communication calls.

[0009] It is also possible to accept the communication request without delay if a total number of communications transmitted simultaneously is less than or equal to a predetermined first threshold value when the detected communication request for the high speed communication is added, to accept the communication request with limiting the transmission rate of the requested communication if the total number of the communications is greater than the first threshold value and is less than or equal to a predetermined second threshold value to transmit the accepted high speed communication at the limited transmission rate, and to reject the communication request when the total number of the communications is greater than the second threshold value.

[0010] In this case, it is also possible to temporarily

hold the communication request for a time period if the total number of the communications is greater than the second threshold value and to accept the communication request after waiting until the total number of the communications becomes less than or equal to the threshold value

[0011] In this control, the traffic of the high speed communications is limited by restricting not only the number of communications but also their rates.

[0012] In a CDMA communication scheme, similar control can be achieved by using transmission power of all the high speed communications transmitted simultaneously, or transmission power of all the communications transmitted simultaneously

[0013] Furthermore, the fixed value, the first threshold value or the second threshold value can be varied in accordance with the number of low speed communications with a transmission rate less than the predetermined rate.

[0014] This makes it possible to adaptively control the upper limit of the traffic of the high speed communications in accordance with the traffic of the low speed communication calls

[0015] Finally, it is possible to carry out channel assignment of a combination of channels whose forward channel transmission rate is higher than a reverse channel transmission rate. This provides an efficient signal transmission method when an information amount of the forward link communications is greater than that of the reverse link communications.

[0016] The present invention can also include a base station implementing these methods.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017]

Fig. 1 is a schematic diagram illustrating cellular mobile communications simultaneously carrying out multiple communications at different transmission rates;

Fig. 2 is a diagram illustrating signal transmission over forward traffic channels in an embodiment in accordance with the present invention;

Fig. 3 is a flowchart of the embodiment in accordance with the present invention;

Fig. 4 is a block diagram showing a configuration of a base station for implementing embodiments in accordance with the present invention;

Fig. 5 is a diagram illustrating a signal transmission method over forward traffic channels in a second embodiment in accordance with the present invention;

Fig. 6 is a flowchart of the second embodiment in accordance with the present invention; and

Figs. 7A and 7B are diagrams illustrating transmission power of a base station in a third embodiment in accordance with the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

[0018] The invention will now be described with reference to the accompanying drawings.

[0019] Fig. 1 is a schematic diagram illustrating cellular mobile communications simultaneously carrying out multiple communications at different transmission rates. In Fig. 1, mobile stations 101-105 are portable phones. The mobile station 101, for example, is carrying out voice communications with a base station 121 with exchanging low speed coded voice signals with the base station. Mobile stations 111-113 are portable information terminals. The portable information terminal 111, for example, is carrying out data communications with a database (not shown) in a fixed network (not shown) through the base station 121.

[0020] In the conventional cellular mobile communications, the voice communications are the mainstream, and hence forward and reverse link signal amounts are nearly the same. In contrast with this, it is likely in the data communications which have been sharply growing recently that a portable information terminal such as the mobile station 111 accesses a database in a fixed network, and receives a great amount of data. In such a case, the reverse link signal sent from the mobile station will be a brief signal requesting the data, whereas the forward link signal transmitted from the base station will be a large amount of requested information, which is much greater in the amount than the reverse link signal. Therefore, it is important to control the forward traffic more efficiently than the reverse traffic.

(FIRST EMBODIMENT)

[0021] Fig. 2 is a diagram illustrating signal transmission over forward traffic channels in the present invention, which illustrates bandwidths of forward traffic channels, and a present state of the channels in use. This example is one of the CDMA mobile communications including two communication types: low speed communications and high speed communications. The high speed communications each use a bandwidth four times that of the low speed communications. When the low speed communications occupy the entire band, it can accommodate 20 communications, whereas when the high speed communications occupy the entire band, it can accommodate five communications.

[0022] In the following description, it is assumed that the upper limit of the high speed communications is two. In the example of Fig. 2, two high speed communications and seven low speed communications are taking place. Although the bandwidth as shown in Fig. 2 can afford to accommodate another new request for the high speed communication, the new request is rejected in the channel allotting method in accordance with the present invention. This is because the total number of the high speed communications becomes three in this case, and hence exceeds the upper limit. Thus, the new

request is canceled as a call loss.

[0023] Low speed communication requests taking place subsequently can be added up to five at a maximum.

[0024] Fig. 3 is a flowchart illustrating the control in the base station 121 when the foregoing upper limit of the high speed communications is set. In Fig. 3, m is the number of the current high speed communications; m_{\max} is the upper limit of the high speed communications (m_{\max} is two in the present embodiment); n is the total number of the current communications expressed in terms of the number of the low speed communications; n_{\max} is the upper limit of the low speed communications the present bandwidth can accommodate when all the communications are the low speed communications; h is a ratio of the transmission rate of the high speed communication to that of the low speed communication ($h = 4$ in the present embodiment); and a is a variable.

[0025] Detecting a communication request from any of the mobile stations 101-105 and 111-113 or from a switching network connected to the base station 121, the base station 121 checks whether the communication request is a high speed communication or not at step S302. If it is the high speed communication, the base station 121 checks whether the current number of the high speed communications (m) plus one is greater than the upper limit of the high speed communications (m_{\max}) at step S312. If it is greater, the base station 121 cancels the high speed communication as a call loss at step S316. If not, the base station 121 sets to the variable a the ratio (h) of the high speed transmission rate to the low speed transmission rate at step S314.

[0026] If the communication request is a low speed communication request, the base station 121 sets the variable a at one at step S304. Then, it adds, to the total number of the current communications (n) expressed in terms of the number of the low speed communications, the value a of the communication request expressed in terms of the number of the low speed communications, and compares it at step S306 with the upper limit (n_{\max}) expressed in terms of the number of the low speed communications that can be accommodated in the bandwidth. If $n+a$ is greater than n_{\max} , the base station 121 cancels the communication request as a call loss at step S316. If not, the base station 121 updates at step S308 the number of the current high speed communications (m) and the total number of the current communications (n) expressed in terms of the number of the low speed communications, and assigns a channel to the communication request at step S310.

[0027] Fig. 4 is a block diagram showing a configuration of a base station 410 for implementing the present embodiment.

[0028] In the forward link communication from the base station to a mobile station, an interface 411 of the base station 410, receiving a new communication request from a communication network 420 connected

to the base station, transfers the signal to a controller 412. The controller 412 makes a decision as to whether it can accept the communication request according to the flowchart in Fig. 3, decides the channel when it can accept it, and transfers to a transmitter and receiver 413 a signal to be transmitted and information about a channel to be used. When the controller 412 cannot accept the communication request, it cancels it as a call loss. The transmitter and receiver 413 transmits the received transmission signal through the assigned channel. The control of the reverse link communication from the mobile station to the base station is carried out in the same manner.

[0029] As for a communication with a data signal that allows delay, the controller 412 holds it for an allowable delay time without canceling it as a call loss even if the controller 412 cannot accept it immediately. If the controller 412 gets ready to accept it while holding it, the controller 412 decides a channel to be used, and transfers to the transmitter and receiver 413 the transmitted signal and information about the channel.

(SECOND EMBODIMENT)

[0030] The second embodiment relates to the control in a base station which can place a speed limit on the high speed communication between the base station and mobile stations. In this case, even if the total number of the high speed communications exceeds a (first) threshold value due to a new high speed communication request, the new communication is allowed with a limited rate. To achieve such control, the base station sets a second threshold value which is greater than the first threshold value, and performs such control that rejects a new high speed communication if the sum total of all the current communications exceeds the second threshold value.

[0031] For example, assume that the first threshold value used for the speed limit is two, and the second threshold value used for the traffic control is 18 expressed in terms of the number of the low speed communications, and that the transmission rate under the speed limit is twice the rate of the low rate communication. In addition, it is assumed that the remaining conditions are the same as those of Fig. 2.

[0032] A new high speed communication request taking place in the conditions as shown in Fig. 2 is not readily accepted because the number of the high speed communications exceeds the first threshold value, but is accepted under the speed limit.

[0033] Fig. 5 illustrates the channel used state when accepting the high speed communication under the speed limit. As illustrated in Fig. 5, the total number of the communications is 17 expressed in terms of the number of the low speed communications, which is less than the second threshold value. Thus, one more speed limited high speed communication and one more low speed communication, or three more low speed com-

munications can be accepted in this case.

[0034] Fig. 6 is a flowchart illustrating the control in the base station in the second embodiment. In Fig. 6, 1 is the total number of the high speed communications with and without the speed limit, which is expressed in terms of the number of the low speed communications; l_{max} is the upper limit of l ($l_{max} = 18$, in this embodiment); g is a ratio of the rate of the speed limited high speed communication to the rate of the low speed communication ($g = 2$ in the present embodiment); and the remaining symbols are the same as those of Fig. 3. This control is also carried out by the controller 412 in the arrangement as shown in Fig. 4.

[0035] In the flowchart of Fig. 6, when a new communication request takes place, the controller 412 decides whether the communication is a high speed communication or not at S602. If it is a high speed communication, the controller 412 checks at step S612 whether the total number of the current high speed communications (m) plus one is greater than the upper limit (m_{max}) of the high speed communications. If it is greater, the controller 412 compares at S616 the sum of l and g with the upper limit l_{max} , where l is the total number of the high speed communications with and without the speed limit, g is the number of the speed limited high speed communications, and l_{max} is the upper limit of the total number of the high speed communications with and without the speed limit, all of which are expressed in terms of the number of the low speed communications. If the sum is greater, the new communication request is canceled as a call loss at step S620. If the sum is smaller, the variable a is set to the ratio g of the rate of the speed limited high speed communication to that of the low speed communication at step S618.

[0036] If the check result at step S612 shows that the total number of the high speed communications does not exceed the upper limit m_{max} , the variable a is set to the ratio (h) of the rate of the high speed communication to that of the low speed communication at step S614.

[0037] If the new communication is a low speed communication, the variable a is set to one at step S604. Subsequently, the controller 412 compares the sum of n and a with n_{max} at step S606, where n is the total number of the current communications expressed in terms of the number of the low speed communications, a is the width of the new communication expressed in terms of the number of the low speed communications, and n_{max} is the acceptable number of communications of the band expressed in terms of the number of the low speed communications. If the sum is greater than n_{max} , the acceptable number of communications of the band expressed in terms of the number of the low speed communications, the new communication request is canceled as a call loss at step S620. On the other hand, if the sum is equal to or less than n_{max} , the controller 412 updates at step S608 the number of the current high speed communications (m), and the total number of all the current communications (n) expressed in terms of

the number of the low speed communications. Then, the controller 412 assigns a channel to the communication request at step S610.

[0038] The present embodiment can also be configured such that it holds, when a communication consists of a data signal allowing delay, the communication for an allowable delay time without canceling the communication as a call loss even if it cannot accept the communication at present, and that if it gets ready to accept the communication while holding the communication, it decides a channel to be used, and transfers the signal to be transmitted and information about the channel.

[0039] Although the value l_{max} is determined in accordance with actual traffic and the bandwidth, the traffic greatly varies depending on an area and time in practice. For example, it is estimated that the ratio of the data communications (high speed communications) increases in a business district during the daytime, and the ratio of the voice communications (low speed communications) is high in a residential district. In the night time, traffic of the business district will sharply reduce, and the ratio of the data communications may increase in the residential district.

[0040] Thus, the appropriate values l_{max} and n_{max} vary depending on the traffic. Taking account of this, a method can be considered for adaptively varying these values in accordance with the traffic. For example, when the ratio of the voice communications is high, the values l_{max} and n_{max} are set at small values, and when the ratio of the voice communications is low, the values l_{max} and n_{max} are set at large values, thereby enabling efficient use of the band independently of the traffic.

[0041] A similar idea is also applicable to the value m_{max} in the first embodiment.

(THIRD EMBODIMENT)

[0042] Actual CDMA mobile communications carry out the transmission power control, and the capacity in terms of the number of users can be limited by the total transmission power. In such a case, it is more effective to control the traffic in accordance with the transmission power rather than the number of the communications. Although increasing transmission power is required with an increase in the transmission rate, the transmission power will vary depending on locations of mobile stations, traffic (an interference amount) of the communications, and the like, even under the same transmission rate.

[0043] The third embodiment in accordance with the present invention controls the reception control of a high speed communication using an upper limit of the transmission power.

[0044] Figs. 7A and 7B shows an example of transmission power conditions of the base station in the third embodiment in accordance with the present invention. In Figs. 7A and 7B, the high speed communications 1 and 2 have the same transmission rate. However, the

mobile station associated with the high speed communication 1 as shown in Fig. 7 is remote from the base station. Therefore, the transmission power of the high speed communication 1 is much greater than that of the high speed communication 2. A new high speed communication request taking place in the state as shown in Fig. 7A is unacceptable because the transmission power of the current high speed communications exceeds the upper limit, and is canceled as a call loss.

[0045] On the other hand, a new high speed communication request taking place in the state as shown in Fig. 7B is acceptable because the transmission power of the current high speed communications is less than the upper limit.

[0046] Although the upper limit is set for the transmission power of the high speed communications in the foregoing example, an upper limit can be set for the transmission power of the high and low speed communications so that the acceptance of the high speed communication can be decided and controlled by the upper limit.

[0047] In the control based on the transmission power, two or more threshold values can be provided to control the communication speed as in the second embodiment. In addition, these threshold values can be dynamically controlled.

[0048] The present embodiment can also be configured such that it holds, when a communication consists of a data signal that allows delay, the communication request for an allowable delay time without canceling the communication as a call loss even if it cannot accept the communication at present, and that when it gets ready to accept the communication while holding it, it decides a channel to be used, and transfers the signal to be transmitted and information about the channel.

[0049] Since a forward link information amount is expected to be greater than a reverse link information amount as described before, efficient assignment of the forward traffic channels must be achieved. Basically, however, it is effective to provide a greater transmission capacity to the forward channels than to the reverse channels, in which case the foregoing signal transmission will further increase the efficiency.

[0050] As described above, the signal transmission method in accordance with the present invention can implement efficient signal transmission over forward traffic channels when carrying out multiple communications with different transmission rates in cellular mobile communications. Since it is expected that the forward link information amount is greater than the reverse link information amount in actual mobile communications, the present signal transmission method is particularly effective when it is applied to the forward traffic channels.

[0051] Applying the high speed communication to the reverse link communications will increase the transmission power of mobile stations. Thus, it is better for reverse links not to assume the high speed communica-

tions, which will serve to reduce the size of the mobile stations. In this case, since the reverse link communications consist of a large number of low speed communications, a large grouping effect can be expected, which will simplify the control without any problem. However, since the forward link communications include the high speed communications, high accuracy traffic control is required, to which the present invention is effectively applicable.

Claims

1. A signal transmission method over a forward traffic channel in cellular mobile communications that can simultaneously perform multiple communications between a plurality of mobile stations and a base station at different transmission rates, said signal transmission method characterized by comprising the steps of:

detecting, on a base station side, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate; and rejecting the communication request for the high speed communication, if a total number of high speed communications transmitted simultaneously exceeds a predetermined fixed value when the detected communication request for the high speed communication is added.

2. A signal transmission method over a forward traffic channel in cellular mobile communications that can simultaneously perform multiple communications between a plurality of mobile stations and a base station at different transmission rates, said signal transmission method characterized by comprising the steps of:

detecting, on a base station side, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate; and accepting the communication request for the high speed communication if a total number of communications transmitted simultaneously is less than or equal to a predetermined fixed value when the detected communication request for the high speed communication is added, temporarily holding the communication request for an allowable time period if the total number is greater than the fixed value, and accepting the communication request after waiting until the total number of the communications becomes less than or equal to the fixed value.

3. A signal transmission method over a forward traffic

channel in cellular mobile communications that simultaneously perform multiple communications between a plurality of mobile stations and a base station at different transmission rates, said signal transmission method characterized by comprising the steps of:

detecting, on a base station side, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;
accepting the communication request for the high speed communication if a total number of communications transmitted simultaneously is less than or equal to a predetermined first threshold value when the detected communication request for the high speed communication is added;
accepting the communication request with limiting a transmission rate of the requested communication if the total number of the communications is greater than the first threshold value and is less than or equal to a predetermined second threshold value, and transmitting the accepted high speed communication at the limited transmission rate; and
rejecting the communication request when the total number of the communications is greater than the second threshold value.

4. A signal transmission method over a forward traffic channel in cellular mobile communications that simultaneously perform multiple communications between a plurality of mobile stations and a base station at different transmission rates, said signal transmission method characterized by comprising the steps of:

detecting, on a base station side, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;
accepting the communication request for the high speed communication if a total number of communications transmitted simultaneously is less than or equal to a predetermined first threshold value when the detected communication request for the high speed communication is added;
accepting the communication request with limiting a transmission rate of the requested communication if the total number of the communications is greater than the first threshold value and is less than or equal to a predetermined second threshold value, and transmitting the accepted high speed communication at the limited transmission rate; and
temporarily holding the communication request

for a time period if the total number is greater than the second threshold value, and accepting the communication request after waiting until the total number of the communications becomes less than or equal to the threshold value.

5. A signal transmission method over a forward traffic channel in CDMA cellular mobile communications that can simultaneously perform multiple communications between a plurality of mobile stations and a base station at different transmission rates, said signal transmission method characterized by comprising the steps of:

detecting, on a base station side, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate; and
rejecting the communication request for the high speed communication, if transmission power of all high speed communications transmitted simultaneously, or transmission power of all communications transmitted simultaneously exceeds a predetermined fixed value when the detected communication request for the high speed communication is added.

6. A signal transmission method over a forward traffic channel in CDMA cellular mobile communications that can simultaneously perform multiple communications between a plurality of mobile stations and a base station at different transmission rates, said signal transmission method characterized by comprising the steps of:

detecting, on a base station side, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate; and
accepting the communication request for the high speed communication if transmission power of all high speed communications transmitted simultaneously or transmission power of all communications transmitted simultaneously is less than or equal to a predetermined fixed value when the detected communication request for the high speed communication is added, temporarily holding the communication request for an allowable time period if the transmission powers are greater than the fixed value, and accepting the communication request after waiting until the transmission power of all high speed communications transmitted simultaneously or the transmission power of all communications transmitted simultaneously becomes less than or equal to the fixed value.

7. A signal transmission method over a forward traffic channel in CDMA cellular mobile communications that can simultaneously perform multiple communications between a plurality of mobile stations and a base station at different transmission rates, said signal transmission method characterized by comprising the steps of:

detecting, on a base station side, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;
accepting the communication request for the high speed communication if transmission power of all high speed communications transmitted simultaneously or transmission power of all communications transmitted simultaneously is less than or equal to a predetermined first threshold value when the detected communication request for the high speed communication is added;
accepting the communication request with limiting a transmission rate of the requested communication if the transmission power of all the high speed communications or the transmission power of all the communications is greater than the first threshold value and is less than or equal to a predetermined second threshold value, and transmitting the accepted high speed communication at the limited transmission rate; and
rejecting the communication request when the transmission power of all the high speed communications or the transmission power of all the communications is greater than the second threshold value.

8. A signal transmission method over a forward traffic channel in CDMA cellular mobile communications that simultaneously perform multiple communications between a plurality of mobile stations and a base station at different transmission rates, said signal transmission method characterized by comprising the steps of:

detecting, on a base station side, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;
accepting the communication request for the high speed communication if transmission power of all high speed communications transmitted simultaneously or transmission power of all communications transmitted simultaneously is less than or equal to a predetermined first threshold value when the detected communication request for the high speed communication is added;

accepting the communication request with limiting a transmission rate of the requested communication if the transmission power of all the high speed communications or the transmission power of all the communications is less than or equal to a predetermined second threshold value, and transmitting the accepted high speed communication at the limited transmission rate; and

temporarily holding the communication request for a time period if the transmission power of all the high speed communications or the transmission power of all the communications is greater than the second threshold value, and accepting the communication request after waiting until the transmission power of all the high speed communications or the transmission power of all the communications becomes less than or equal to the threshold value.

9. The signal transmission method as claimed in claim 1, 2, 5 or 6, further characterized by comprising the step of varying the fixed value in accordance with a number of low speed communications with a transmission rate less than the predetermined rate.
10. The signal transmission method as claimed in claim 3, 4, 7 or 8, further characterized by comprising the step of varying the first threshold value and/or second threshold value in accordance with a number of low speed communications with a transmission rate less than the predetermined rate.
11. The signal transmission method as claimed in any one of claims 1-10, further characterized by comprising the step of carrying out channel assignment of a combination of channels whose forward channel transmission rate is higher than a reverse channel transmission rate.
12. A base station that simultaneously performs multiple communications with a plurality of mobile stations at different transmission rates, said base station characterized by comprising:

a high speed communication detector for detecting, when receiving a communication request, whether the communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;
a threshold detector for detecting, in response to detection of the high speed communication by said high speed communication detector, whether a total number of high speed communications transmitted simultaneously exceeds a predetermined fixed value if the detected high speed communication is added; and

a controller for controlling reception of the high speed communication request in response to detection by said threshold detector, wherein said controller rejects the high speed communication request if the total number of the high speed communications transmitted simultaneously exceeds the predetermined fixed value.

13. A base station that simultaneously performs multiple communications with a plurality of mobile stations at different transmission rates, said base station characterized by comprising:

a high speed communication detector for detecting, when receiving a communication request, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;

a detector for detecting, in response to detection of the high speed communication by said high speed communication detector, whether a total number of high speed communications transmitted simultaneously exceeds a predetermined fixed value if the detected high speed communication is added;

a holder for temporarily holding the communication request for an allowable time period in response to detection by said detector that its detection result is greater than the fixed value; and

a controller for controlling reception of the high speed communication request in response to said detector and said holder, wherein said controller accepts, when the total number of the high speed communications transmitted simultaneously exceeds the predetermined fixed value, the high speed communication request after waiting within an allowable time period until the total number of the high speed communications becomes less than or equal to the fixed value.

14. A base station that simultaneously performs multiple communications with a plurality of mobile stations at different transmission rates, said base station characterized by comprising:

a high speed communication detector for detecting, when receiving a communication request, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;

a first threshold detector for detecting, in response to detection of the high speed communication by said high speed communication

detector, whether a total number of high speed communications transmitted simultaneously exceeds a predetermined first threshold value if the detected communication request for the high speed communication is added;

a second threshold detector for detecting, in response to detection by said first threshold detector that the total number is greater than the first threshold value, whether the total number is equal to or less than a predetermined second threshold value; and

a controller for controlling reception of the high speed communication request in response to said first threshold detector and said second threshold detector,

wherein said controller immediately accepts the communication request when the total number of the high speed communications transmitted simultaneously is equal to or less than the predetermined first threshold value, accepts the communication request with limiting a transmission rate of the requested communication if the total number of the high speed communications is greater than the first threshold value and is less than or equal to the predetermined second threshold value, and rejects the communication request when the total number of the high speed communications transmitted simultaneously is greater than the second threshold value.

15. A base station that simultaneously performs multiple communications with a plurality of mobile stations at different transmission rates, said base station characterized by comprising:

a high speed communication detector for detecting, when receiving a communication request, whether the communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;

a first threshold detector for detecting, in response to detection of the high speed communication by said high speed communication detector, whether a total number of high speed communications transmitted simultaneously exceeds a predetermined first threshold value if the detected communication request for the high speed communication is added;

a second threshold detector for detecting, in response to detection by said first threshold detector that the total number is greater than the first threshold value, whether the total number is equal to or less than a predetermined second threshold value;

a holder for temporarily holding the high speed communication request for an allowable time

period in response to detection by said second threshold detector that its detection result is greater than the second threshold value; and a controller for controlling reception of the high speed communication request in response to said first threshold detector, said second threshold detector and said holder, wherein said controller immediately accepts the communication request when the total number of the high speed communications transmitted simultaneously is equal to or less than the predetermined first threshold value, accepts the communication request with limiting a transmission rate of the requested communication if the total number of the high speed communications is greater than the first threshold value and is less than or equal to the predetermined second threshold value, and holds, in response to detection by said second threshold detector that the total number exceeds the second threshold value, the high speed communication request for an allowable time period, and waits until the total number of the high speed communications becomes less than or equal to the second threshold value.

16. A base station that simultaneously performs multiple CDMA communications with a plurality of mobile stations at different transmission rates, said base station characterized by comprising:

a high speed communication detector for detecting, when receiving a communication request, whether the communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;
 a detector for detecting, in response to detection of the high speed communication by said high speed communication detector, whether transmission power of all high speed communications transmitted simultaneously or transmission power of all communications transmitted simultaneously exceeds a predetermined fixed value if the detected high speed communication is added; and
 a controller for controlling reception of the high speed communication request in response to detection by said threshold detector, wherein said controller rejects the high speed communication request if the transmission power of all high speed communications transmitted simultaneously or transmission power of all communications transmitted simultaneously exceeds the predetermined fixed value.

17. A base station that simultaneously performs multiple CDMA communications with a plurality of

mobile stations at different transmission rates, said base station characterized by comprising:

a high speed communication detector for detecting, when receiving a communication request, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;
 a detector for detecting, in response to detection of the high speed communication by said high speed communication detector, whether transmission power of all high speed communications transmitted simultaneously or transmission power of all communications transmitted simultaneously exceeds a predetermined fixed value if the detected high speed communication is added;
 a holder for temporarily holding the communication request for an allowable time period in response to detection by said detector that its detection result is greater than the fixed value; and
 a controller for controlling reception of the high speed communication request in response to said detector and said holder, wherein said controller accepts the communication request when the transmission power of all the high speed communications transmitted simultaneously or the transmission power of all the communications transmitted simultaneously is equal to or less than the predetermined fixed value if the high speed communication is added, holds the communication request for an allowable time period when the transmission power exceeds the fixed value, and accepts the communication request after waiting within an allowable time period until the transmission power of all the high speed communications transmitted simultaneously or the transmission power of all the communications transmitted simultaneously becomes less than or equal to the fixed value.

18. A base station that simultaneously performs multiple communications with a plurality of mobile stations at different transmission rates, said base station characterized by comprising:

a high speed communication detector for detecting, when receiving a communication request, whether a communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;

a first threshold detector for detecting, in response to detection of the high speed communication by said high speed communication

detector, whether transmission power of all high speed communications transmitted simultaneously or transmission power of all communications transmitted simultaneously exceeds a predetermined first threshold value if the detected communication request for the high speed communication is added;

a second threshold detector for detecting, in response to said first threshold detector, whether the transmission power of all the high speed communications transmitted simultaneously or the transmission power of all the communications transmitted simultaneously exceeds a predetermined second threshold value if the requested communication is added; and

a controller for controlling reception of the high speed communication request in response to said first threshold detector and said second threshold detector,

wherein said controller accepts the communication request when the transmission power of all the high speed communications transmitted simultaneously or the transmission power of all communications transmitted simultaneously is equal to or less than the predetermined first threshold value,

accepts the communication request with limiting a transmission rate of the requested communication if the transmission power of all the high speed communications or the transmission power of all the communications is greater than the first threshold value and is less than or equal to the predetermined second threshold value, and

rejects the communication request when the transmission power of all the high speed communications or the transmission power of all the communications is greater than the second threshold value.

19. A base station that simultaneously performs multiple CDMA communications with a plurality of mobile stations at different transmission rates, said base station characterized by comprising:

a high speed communication detector for detecting, when receiving a communication request, whether the communication request is made for a high speed communication with a transmission rate higher than a predetermined rate;

a first threshold detector for detecting, in response to detection of the high speed communication by said high speed communication detector, whether transmission power of all high speed communications transmitted simultaneously or transmission power of all commu-

nications transmitted simultaneously exceeds a predetermined first threshold value if the detected communication request for the high speed communication is added;

a second threshold detector for detecting, in response to said first threshold detector, whether the transmission power of all the high speed communications transmitted simultaneously or the transmission power of all the communications transmitted simultaneously exceeds a predetermined second threshold value if the requested communication is added; a holder for temporarily holding the communication request for an allowable time period in response to said second threshold detector; and

a controller for controlling reception of the high speed communication request in response to said first threshold detector, said second threshold detector and said holder, wherein said controller accepts the communication request when the transmission power of all the high speed communications transmitted simultaneously or the transmission power of all the communications transmitted simultaneously is equal to or less than the predetermined first threshold value if the requested high speed communication is added, accepts the communication request with limiting a transmission rate of the requested communication if the transmission power of all the high speed communications or the transmission power of all the communications is greater than the first threshold value and is less than or equal to the predetermined second threshold value, and transmits the accepted high speed communication at the limited transmission rate, temporarily holds the communication request when the transmission power of all the high speed communications or the transmission power of all the communications exceeds said second threshold value, and transmits a signal after waiting within an allowable time period until the transmission power of all the high speed communications or the transmission power of all the communications becomes less than or equal to said second threshold value.

20. The base as claimed in claim 12, 13, 16 or 18, further characterized by comprising means for varying the fixed value in accordance with a number of low speed communications with a transmission rate less than the predetermined rate.

21. The signal transmission method as claimed in claim 14, 15, 18 or 19, further characterized by comprising means for varying the first threshold value and/or second threshold value in accordance with a

number of low speed communications with a transmission rate less than the predetermined rate.

5

10

15

20

25

30

35

40

45

50

55




FIG.1





FIG.2

**FIG.3**




FIG.4




FIG.5




FIG. 6




FIG. 7A




FIG. 7B

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP98/03666

A. CLASSIFICATION OF SUBJECT MATTER Int.Cl ⁶ H04Q7/28, H04J13/00		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) Int.Cl ⁶ H04B7/24-7/26, H04Q7/00-7/38, H04J13/00-13/06		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1926-1998 Toroku Jitsuyo Shinan Koho 1994-1998 Kokai Jitsuyo Shinan Koho 1971-1998 Jitsuyo Shinan Toroku Koho 1996-1998		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP, 07-312783, A (NTT Mobile Communications Network Inc.), 28 November, 1995 (28. 11. 95) & US, 5586113, A & US, 5734648, A	1-21
A	JP, 07-038963, A (Matsushita Electric Industrial Co., Ltd.), 7 February, 1995 (07. 02. 95) & US, 5583851, A	1-21
A	JP, 09-036801, A (NEC Corp.), 7 February, 1997 (07. 02. 97) & US, 5794129, A	1-21
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 12 November, 1998 (12. 11. 98)		Date of mailing of the international search report 24 November, 1998 (24. 11. 98)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)